

Hyperchill

Industrial Process Chillers for Precision Cooling



Extremely compact and easy to use, Hyperchill ensures an accurate control of water temperature. Each model is designed for safe and reliable operation in the most varied working conditions, thanks to the modern technical solutions used and the availability of a wide range of accessories and options.

Each individual Hyperchill unit is extensively tested to guarantee efficient operation and reliability in all working conditions.



Benefits

Complete solution, easy to install and manage

- Hydraulic circuit: water tank, immersed evaporator, pump with bypass provide a compact and easy to install solution.
- Electronic controllers with proprietary software provide access to all the parameters of the units and allow special management for any specific need.
- Available with remote monitoring.
- Completely configurable with many options and kits to fit many industrial applications needs.
- Condenser filters.
- Independent condensing plenum.
- Full access and easy service design.

High reliability and back-up eliminate downtime

- Large water tanks allow minimum compressor cycling and precise temperature control.
- Double independent fridge circuits.
- 4 compressors (2 per each fridge circuit) with automatic rotation.
- Double standby water pumps available.
- Maximum ambient temperature up to 45°C.

Lowest energy consumption in the market

- Oversized condensers and evaporators.
- Use of compliant scroll compressors.

Process Cooling Applications

- Extruders
- Surface Processing
- Welding Engineering
- Blow Mould Machines
- Printing Systems
- Coating Systems
- Chemical and Pharmaceutical
- Plastics Processing
- Thermoform Machines
- Plasma Coating
- Medical Imaging
- Food and Beverage Industry
- Injection Moulding
- Electroplating Baths
- Bioenergy
- Compressed Air
- Hydrogen



ENGINEERING YOUR SUCCESS.

Features and Benefits

- **Water and refrigerant manometers:** permit full control of the working conditions.
- **Microprocessors:** permit full control of the unit parameters. Proprietary software allows a wide range of programming and remote monitoring options.
- **Compliant scroll compressors:** with less moving parts and compliant technology provide excellent efficiency, high reliability, and very low noise levels.
- **Air cooled with axial fans:** suitable for outdoor installation, no need for protection.
- **Water pump (standard 3 bar):** different head-pressures available to meet the requirements of specific applications. Configurable as a twin-system for 100% back-up.



- **Mesh filters:** condenser protection from dirt and contamination, reduces maintenance costs and the risk of downtime.
- **Evaporator:** located inside the water tank - reduces the overall dimensions, increases the efficiency and improves temperature control.
- **Water bypass:** protects the pump and supplies constant flow to the evaporator avoiding alarms and freezing.
- **Water tank:** generously dimensioned to guarantee high reliability and improved temperature control.

Versions

- **Water cooled** alternative to air cooled versions, shell and tube condensers with pressostatic valves.
- **Low ambient** temperature additional condensing control for continuous operation in cold ambients (negative temperature). Available for air cooled, axial fan units.
- **Low water** temperature for negative water temperature control, down to -10°C.
- **Non ferrous** stainless steel tank, pump, and hydraulic components.
- **Bioenergy:** epoxy coating on all exposed copper as protection against aggressive environments.
- **Special and multiple pumps:** higher (P50-5bar) or lower (P15-1,5bar) head pressure available to suit different hydraulic circuits. Double stand-by pump for high reliability.
- **Antifreeze** heating avoids freezing when the unit is switched off and glycol is not used.



Water Cooled Hyperchill ICE

Options

- **Remote control kits:** base version for remote ON/OFF and general alarm monitoring. Advanced version for complete remote unit management.
- **MODBUS RTU** kit available on request.



- **Water fill kits:** pressurized, automatic or ambient manual kits, for water filling in any installation.



Technical Data

Model ICE		150	183	230	310	360
Cooling capacity ¹	kW	149.2	182.3	228	309	360
Compressor abs. power ¹	kW	30.8	40.1	51.4	65	82
SEPR HT ³		5.35	5.04	5.02	5.51	5.73
Power supply	V/ph/Hz	400/3/50 no neutral				
Protection index		54				
Refrigerant		R407C				

Compressors

Type		Hermetic scroll				
Compressors/circuits		4/2				
Max abs. power - 1 comp.	kW	11.1	13.7	16.8	23.3	28.7

Axial Fans

Quantity	n°	2		3	4	
Max abs. Power - 1 fan	kW	2	2	2	2	2
Air flow	m³/h	47000	46000	66000	88000	88000

Water Cooled Version

Condenser water flow	m³/h	19.2	31.0	33.0	N.A.	
Condensers connections	in	1¼"	1¼"	1½"		

Pump P30

Max abs. power	kW	4.5	4.5	4.5	8.4	8.4
Water flow (nom/max) ¹	m³/h	25/50	30/50	39/50	53/90	62/90
Head pressure (nom/min) ¹	m H ₂ O	34/20	32/20	26/20	26/19	23/19

Weight and Dimensions

Width	mm	1287	1287	1287	1500	1500
Depth	mm	3000	3000	3260	4200	4200
Height	mm	2298	2298	2298	2240	2240
Connections in/out	in	2½"	2½"	2½"	4"	4"
Tank capacity	l	1000	1000	1000	400	400
Weight (axial)	kg	1500	1800	2100	2900	3100
Weight (centrif.)	kg	1700	2000	2300	N.A.	
Weight (water cooled)	kg	1500	1800	2100		

Noise Level

Sound pressure (axial) ²	dB(A)	62	62	64	65	65
-------------------------------------	-------	----	----	----	----	----

1) At water in/out temperature = 20/15°C, glycol 0%, either 25°C ambient temperature (air-cooled models) or 25°C condenser water inlet temperature with 35°C condensing temperature water-cooled models).

2) Referred to axial fan version in free field conditions at a distance of 10m from unit, measured on condenser side, 1 m from ground.

3) Value calculated in accordance with the European regulation (EU) 2016/2281 with regards to Ecodesign requirements for high temperature process chillers.

As the manufacturer of process chillers delivering water at a design temperature of 15°C, Parker Hannifin Manufacturing s.r.l., Gas Separation and Filtration Division EMEA, declares that Parker chillers are exempt from Ecodesign EU regulation 2016/2281.

Correction factors

A) Ambient temp. (air-cooled models)	°C	5	10	15	20	25	30	35	40	45
Correction factor (f1)		1.05	1.05	1.05	1.05	1	0.95	0.89	0.83	0.77
B) Water outlet temperature	°C	5		10		15		20		25
Correction factor (f2)		0.72		0.86		1		1		1
C) Glycol	%	0		10		20		30		40
Correction factor (f3)		1		0.99		0.98		0.97		0.96
D) Condenser water inlet temp. (water-cooled models)	°C	20		25		30		35		40
Correction factor (f4)		1.05		1		0.95		0.9		0.85

To obtain the required cooling capacity multiply the value at nominal conditions by the above correction factors (i.e. cooling capacity = Pxf1xf2xf3xf4, where P is the cooling capacity at conditions (1)).

Hyperchill, in its standard configuration, can operate up to ambient temperatures of max 45°C and min. 5°C and water temperatures of max 30°C inlet and min. 0°C outlet. The above correction factors are approximative: for a precise selection always refer to the software selection programme.



Direct Cooling Solutions Ltd

Unit 38, Herald Way, Binley Industrial Estate,
Coventry CV3 2RQ

Website: www.directcoolingsolutions.co.uk

Email: enquiries@directcoolingsolutions.co.uk

Telephone: 0808 175 9388